

2-Channel Analog Input Module 0-10 V single-ended (S.E.)




Fig. Series 750 / Technical data see page 28 / Delivery without Mini WSB marker
Series 750 / 753 marking see pages 16 ... 17 / 18 ... 19

The analog input module receives signals with the standardized values of 0-10 V.

The input signal is electrically isolated and will be transmitted with a resolution of 12 bits.

The internal system supply is used for the power supply of the module.

The input channels of a module have one common ground potential.

The shield (screen) is directly connected to the DIN rail.

Description	Item no.	Pack. unit
2AI 0-10V DC S.E.	750-467	10 ¹⁾
2AI 0-10V DC S.E. S5 ²⁾	750-467/000-200	1
2AI 0-10V DC S.E. (without connector)	753-467	10 ¹⁾
¹⁾ Also available individually		
²⁾ Data format for S5 control with FB 251		
Accessories	Item no.	Pack. unit
753 Series connector	753-110	25
Coding elements	753-150	100
Miniature WSB quick marking system,		
plain	248-501	5
with marking	see pages 256 ... 257	
Approvals		
Series 750 and 753		
Conformity marking	CE	
UL 508		
ANSI/ISA 12.12.01	Class I, Div. 2, Grp. ABCD, T4	
Series 750		
EN 60079-15	I M2 / II 3 GD Ex nA IIC T4	

Technical Data	
No. of inputs	2
Voltage supply	via system voltage DC/DC
Current consumption typ. (internal)	60 mA
Input voltage (max.)	35 V
Signal voltage	0 ... 10 V
Internal resistance	130 kΩ
Resolution	12 bits
Conversion time (typ.)	2 ms
Measuring error (25 °C)	≤ ± 0.2 % of the full scale value
Temperature coefficient	< ± 0.01 % / K of the full scale value
Isolation	500 V system/supply
Bit width	2 x 16 bits data
	2 x 8 bits control/status (optional)
Wire connection	CAGE CLAMP®
Cross sections	0.08 mm² ... 2.5 mm² / AWG 28 ... 14
Stripped lengths (750 / 753 Series)	8 ... 9 mm / 0.33 in
	9 ... 10 mm / 0.37 in
Width	12 mm
Weight	51.5 g
EMC CE-Immunity to interference	acc. to EN 50082-2 (1996)
EMC CE-Emission of interference	acc. to EN 50081-1 (1993)