JUMPFLEX® Relay Socket with Solid State Relay

	Solid state relay **Input: 230 V AC/DC** **Output: 0 V ... 24 V DC / 2 A**	







Description	Item No.	Pack. Unit	
***JUMPFLEX*® relay socket with solid state relay, for DIN 35 rail**	**857-728**	1	

Technical Data

Accessories see pages 62 ... 63

Control circuit:	
Nominal input voltage (V_N)	230 V AC/DC
Input voltage range	U_N -15 % ... +10 %
Nominal input current (I_N)	3 mA
Load circuit:	
Switching voltage	0 V ... 24 V DC
Peak reverse voltage	33 V
Max. switching current	2 A DC
Forward voltage at max. switching current	< 120 mV DC
Ambient operating temperature	-20 °C ... +60 °C
Storage temperature	-40 °C ... +70 °C
Dielectric strength control/switching circuit	2.5 kV
Dimensions (mm) W x H x L	6 x 81 x 94
	Height from upper-edge of DIN 35 rail
Wire connection	CAGE CLAMP®S
Cross sections	solid: 0.08 mm² ... 2.5 mm² / AWG 28 ... 12
	fine-stranded: 0.34 mm² ... 2.5 mm² / AWG 22 ... 12
Stripped lengths	9 ... 10 mm / 0.37 in