

WAGO-Industrial-Eco-Switches

Industrial Switch, 5 Ports 100BASE-TX

852-111/000-001



© 2023 WAGO GmbH & Co. KG
All rights reserved.

WAGO GmbH & Co. KG

Hansastraße 27
D - 32423 Minden

Phone: +49 571/887 – 0
Fax: +49 571/887 – 844169
E-Mail: ✉ info@wago.com
Internet: 🌐 www.wago.com

Technical Support

Phone: +49 571/887 – 44555
Fax: +49 571/887 – 844555
E-Mail: ✉ support@wago.com

Every conceivable measure has been taken to ensure the accuracy and completeness of this documentation. However, as errors can never be fully excluded, we always appreciate any information or suggestions for improving the documentation.

E-Mail: ✉ documentation@wago.com

We wish to point out that the software and hardware terms as well as the trademarks of companies used and/or mentioned in the present manual are generally protected by trademark or patent.

WAGO is a registered trademark of WAGO Verwaltungsgesellschaft mbH.

Table of Contents

Provisions	5
1.1 Intended Use	5
1.2 Typographical Conventions	6
1.3 Legal Information	8
Safety	9
2.1 General Safety Regulations	9
2.2 Electrical Safety	9
2.3 Mechanical Safety	9
2.4 Thermal Safety	9
2.5 Indirect Safety	10
Overview	11
Properties	12
4.1 Views	12
4.1.1 Front View	12
4.1.2 Top View	12
4.2 Type Plate	13
4.3 Connections	14
4.3.1 Supply Voltage	14
4.4 Display Elements	14
4.4.1 Status LED of the Supply Voltage	14
4.4.2 LED Indicators – Network Connections	14
Planning	15
5.1 Data Security	15
5.2 Line Depth	15
5.3 Installation Location and Additional Enclosure	16
5.4 Ground Conductor and Protective Ground	16
5.5 Mounting Position	16
5.6 EMC Installation	17
Transport and Storage	18
Installation and Removal	19
7.1 Mounting on the DIN-Rail	19
7.2 Removal from the DIN-Rail	19
7.3 Screw Installation on a Flat Surface	20
7.4 Dimensions of the Mounting Holes	20
Anschließen	21
Decommissioning	22

9.1 Disposal and Recycling	22
Appendix	23
10.1 Technical Data, Approvals, Guidelines and Standards	23
10.1.1 Datenblatt_852-111/0000-0001	24
10.2 RJ-45 Cable.....	26
10.3 Protected Rights	26

Provisions

This document applies to the following product:

852-111/000-001 (Industrial ECO Switch; 5 100Base-TX ports)

Product detail page	www.wago.com/852-111/000-001
Hardware version	01 and above
Firmware version	02 and above

The product must only be installed and operated in accordance with the operating instructions. Knowledge of the operating instructions is required for proper use. You can find all documents and information on the detailed product page.

1.1 Intended Use

This product is for setting up ETHERNET networks.

The product is an open type device and is designed for installation in an additional enclosure.

- This product is intended for installation in automation technology systems.
- Operation of the products in industrial area is permitted.
- The product is designed for use in dry indoor rooms.
- Operation of the product in other application areas is only permitted when corresponding approvals and labeling are present.

Improper Use

Improper use of the product is not permitted. Improper use occurs especially in the following cases:

- Non-observance of the intended use
- Use without protective measures in an environment in which moisture, salt water, salt spray mist, dust, corrosive fumes, gases, direct sunlight or ionizing radiation can occur
- Use of the product in areas with special risk that require continuous fault-free operation and in which failure of or operation of the product can result in an imminent risk to life, limb or health or cause serious damage to property or the environment (such as the operation of nuclear power plants, weapons systems, aircraft and motor vehicles)

Warranty and Liability

The terms set forth in the General Business and Contract Conditions for Delivery and Service of WAGO GmbH & Co. KG and the terms for software products and products with integrated software stated in the WAGO Software License Contract – both available at

www.wago.com – shall apply. In particular, the warranty is void if:

- The product is improperly used.
- The deficiency (hardware and software configurations) is due to special instructions.
- Modifications to the hardware or software have been made by the user or third parties that are not described in this documentation and that has contributed to the fault.

Individual agreements always have priority.

Obligations of Installers/Operators

Installers and operators bear responsibility for the safety of an installation or a system assembled with the product. The installer/operator is responsible for the proper installation and safety of the system. All laws, standards, guidelines, local regulations and accepted technological standards and practices applicable at the time of installation, as well as the products' operating instructions, must be followed. In addition, the installment requirements for approval must be met. In the event of non-compliance, operation of product within the scope of the approval is not permitted.

In addition, the installer/operator is responsible for the deployment of suitable personnel.

1.2 Typographical Conventions





Number Notation

100	Decimals: Normal notation
0x64	Hexadecimals: C-notation
'100'	Binary: In single quotation marks
'0110.0100'	Nibbles separated by a period

Text Formatting

<i>italic</i>	Names of paths or files
bold	Menu items, entry or selection fields, emphasis
Code	Sections of program code
>	Selection of a menu point from a menu
"Value"	Value entries
[F5]	Identification of buttons or keys

Cross References / Links

	Cross references/links to a topic in a document
	Cross references / links to a separate document
	Cross references / links to a website
	Cross references / links to an email address

Sequence of Action

- ✓ This symbol identifies a precondition.
- 1. Action step
- 2. Action step
 - ⇒ This symbol identifies an intermediate result.
 - ⇒ This symbol identifies the result of an action.
- Individual action step

Lists

- Lists, first level

- Lists, second level

Figures

Figures in this documentation are for better understanding and may differ from the actual product design.

Warning Notices

DANGER

Type and source of hazard

Indicates an imminently hazardous situation which, if not avoided, will result in death or serious injury.

- Action step to reduce risk

WARNING

Type and source of hazard

Indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.

- Action step to reduce risk

CAUTION

Type and source of hazard

Indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury.

- Action step to reduce risk

NOTICE

Type and source of malfunction (property damage only)

Indicates a potentially hazardous situation which, if not avoided, may result in damage to property.

- Action step to reduce risk

Information Notices

Note

Information


Indicates information, clarifications, recommendations, referrals, etc.

1.3 Legal Information

Intellectual property

The intellectual property of this document belongs to WAGO GmbH & Co. KG. The reproduction and distribution of its content (in whole or in part) is prohibited, unless otherwise provided by statutory provisions, written agreements or this document. In case of doubt, the written consent of WAGO GmbH & Co. KG must be obtained in advance.


Third-party products are always mentioned without any reference to patent rights. WAGO GmbH & Co. KG, or the manufacturer of third-party products, retains all rights regarding patent, utility model or design registration.

Third-party trademarks are referred to in the product documentation. The “®” and “™” symbols are omitted hereinafter. The trademarks are listed in the Appendix:  **Protected Rights [▶ 26]**.

Subject to Change

The instructions, guidelines, standards, etc., in this manual correspond to state of the art at the time the documentation was created and are not subject to updating service. The installer and operator bear sole responsibility to ensure they are complied with in their currently applicable form. WAGO GmbH & Co. KG retains the right to carry out technical changes and improvements of the products and the data, specifications and illustrations of this manual. All claims for change or improvement of products that have already been delivered – excepting change or improvement performed under guarantee agreement – are excluded.

Licenses

The product may contain open-source software. The requisite license information is saved in the product. This information is also available under  www.wago.com.

Safety

2.1 General Safety Regulations

- This documentation is part of the product. Therefore, retain the documentation during the entire service life of the product. Pass on the documentation to any subsequent user of the product. In addition, ensure that any supplement to this documentation is included, if necessary.
- The product must only be installed and put into operation by qualified electrical specialists per EN 50110-1/-2 and IEC 60364.
- Changes to switch configurations in the network must always be performed by qualified personnel with sufficient skills.
- Comply with the laws, standards, guidelines, local regulations and accepted technology standards and practices applicable at the time of installation.

2.2 Electrical Safety

- Make sure the product does not carry any voltage before starting work.

Power Supply

- Connecting impermissible current or frequency values may destroy the product.

Grounding/Protection/Fuses

- When handling the product, please ensure that environmental factors (personnel, work space and packaging) are properly equalized. Do not touch any conducting parts.

Cables

- Maintain spacing between control, signal and data lines and the power supply lines.
- Observe permissible temperature range of connecting cables.
- Only one conductor may be connected to each connection point (e.g., CAGE CLAMP® connection).
- Use appropriate strain relief.

2.3 Mechanical Safety

- Before startup, please check the product for any damage that may have occurred during shipping. Do not put the product into operation in the event of mechanical damage.
- Do not open the product housing.
- Avoid conductive contamination.

2.4 Thermal Safety

- The surface of the housing heats up during operation. Under special conditions (e.g., in the event of a fault or increased surrounding air temperature), touching the product may cause burns. Allow the product to cool down before touching it.
- If the surface temperature of the product can exceed 40 °C, wear protective gloves and attach protective covers and/or touch-proof protection.

- The temperature inside the additional enclosure must not exceed the surrounding air temperature permitted for the mounted product.
- Cooling of the product must not be impaired. Ensure air can flow freely and that the minimum clearances from adjacent products/areas are maintained.

2.5 Indirect Safety

- Do not use any contact spray for cleaning.
- Do not use hard objects that could cause scratches for cleaning.
- The product is not resistant to materials with seeping and insulating properties, such as aerosols, silicones or triglycerides (found in some hand creams). If these substances occur in the environment of the product, install the product in an additional housing that is resistant to these substances as well.
- Observe possible different technical specifications for mounting that does not correspond to the nominal mounting position.
- Only use accessories authorized by WAGO.

Overview

This product is an unmanaged industrial ETHERNET switch with five 10/100BASE-TX ports for easily setting up small- to medium-sized networks. Its compact design with a DIN-rail adapter makes installation in control cabinets easier and provides high vibration and shock resistance. Additionally, automatic transmission rate detection (auto-negotiation) and automatic detection of the transmit and receive lines (Auto MDI-X) allow simple plug-and-play operation.

Switching Technology

Industrial ETHERNET primarily uses switching technology. This technology allows any network subscriber to send at any time, because the subscriber always has an open peer-to-peer connection to the next switch. The connection is bidirectional, i.e., the subscriber can send and receive at the same time (full duplex operation). Targeted use of switching technology can increase real-time capability, because the peer-to-peer connection prevents collisions in network communication.

Auto-Negotiation

Auto-negotiation allows two interconnected ETHERNET ports to independently set the highest possible transmission rate and transmission type for their communication link. Auto-negotiation is available to ETHERNET subscribers connected to the switch via a twisted pair cable.

Autocrossing

Autocrossing (Auto-MDI/MDI-X, "Medium Dependent Interface") automatically reconfigures the receive and transmit signals for twisted-pair interfaces as needed. This allows users to use wired and crossover cables in the same manner one-to-one.

Store-and-Forward Switching Mode

WAGO's industrial switches operate in store-and-forward switching mode. In this mode, the ETHERNET switch caches the entire data telegram and uses the CRC checksum to verify its correctness and validity. If there are no errors, the data telegram is queued and forwarded to the destination address using the MAC table. Faulty or damaged data telegrams are not further distributed in the network. The delay the data telegram requires in order to pass the store-and-forward switch depends on the telegram length.

Properties

4.1 Views

4.1.1 Front View




Figure 1: Front View

1	10/100BASE-TX ports	RJ-45 Cable [▶ 26]
2	Status LED: speed	LED Indicators – Network Connections [▶ 14]
3	Status LED: TX-port LNK/ACT	LED Indicators – Network Connections [▶ 14]

4.1.2 Top View




Figure 2: Top View

1	Plug (male header) for power consumption	Supply Voltage [▶ 14]
2	Status LED: supply voltage	Display Elements [▶ 14]
3	Grounding screw	Ground Conductor and Protective Ground [▶ 16]

4.2 Type Plate












Figure 3: Type Plate (Example)

No.	Name	Description
1		WAGO logo and address
2		Field for names
		With the CE mark, WAGO declares that the product meets the applicable requirements as set out in Community harmonization legislation per EC Regulation 765/2008, which allows the product to carry this mark.
		The UKCA (UK Conformity Assessed) mark declares that the conformity requirements for the UK market are met.
		With the FCC marking, WAGO declares conformity with the regulations of the US Federal Communications Commission.
		Certified safety mark of UL-listed products for the American and Canadian market
3	Item No.	Item number
4	Serial No.	Product serial number as a barcode
5	Serial No.	Product serial number in text form: <Serial number> <Firmware version> (left sequence of digits; example: 02) <Hardware version> (right sequence of digits; example: 09)
6	IN:	Indicates the supply voltage 🔗 Technical Data, Approvals, Guidelines and Standards [▶ 23]
7		QR code with link to product detail page <a href="http://www.wago.com/<item number>">www.wago.com/<item number>
8		Field for warning and information symbols
		Caution: Do not touch hot surfaces!
		Note: Electrical and electronic equipment must not be disposed of with household waste! More information about this topic: 🔗 Disposal and Recycling [▶ 22]
		Note: Observe the product documentation!

4.3 Connections

4.3.1 Supply Voltage




Figure 4: Power Supply Connection

Connection	Description
+	Plus potential
-	Minus potential
⏏	Ground potential (functional ground)

4.4 Display Elements

4.4.1 Status LED of the Supply Voltage



Figure 5: Status LED

LED	Designation	State	Description
PWR	Status LED: supply voltage	Green	Power supply in use
		Off	Power supply switched off or error

4.4.2 LED Indicators – Network Connections




Figure 6: LED Indicators – Network Connections

Designation	Color	State	Description
100	Green	On	100 Mbit/s connection
		Off	10 Mbit/s or no connection
LNK/ACT	Green	On	Port running at 10 or 100 Mbit/s
		Flickering	Data packet transfer active
		Off	No connection

Planning

5.1 Data Security

Professional planning and design is an important requirement for securing data confidentiality, availability and integrity.

Random Influences

Data transmission and processing can be disrupted by random influences, such as temporary electromagnetic disturbances. Proper setup can significantly reduce the likelihood of corruption or destruction of data.

For additional information see:  [EMC Installation \[▶ 17\]](#).

Deliberate Influences

Use in ETHERNET Areas

ETHERNET products are designed for use in local networks. Please note the following when using ETHERNET products in your system:

- Do not connect control components and control networks to an open network such as the Internet or an office network.
WAGO recommends putting control components and control networks behind a fire-wall.
- In the control components, close all ports and services not required by your application to minimize the risk of cyber attacks and to enhance cybersecurity.
Only open the ports and services for the duration of the commissioning/configuration.
- Limit physical and electronic access to all automation components to authorized personnel only.
- To reduce the risk of unauthorized access to your system, change the default passwords during initial commissioning.
- To reduce the risk of unauthorized access to your system, regularly change the passwords used.
- To verify that the measures taken meet your security requirements, regularly perform threat analyses.
- To restrict access to and control of individual products and networks, employ a “defense-in-depth” mechanism in your system’s security configuration.

Additional document

-  [White Paper Cybersecurity in Production Facilities](#)

All the documentation and information is available at:  www.wago.com.

5.2 Line Depth

Line Depth for PROFINET

This product meets the requirements of PROFINET Conformance Class A. The line depth (cascading) is the number of all switches in a communication path. The maximum line depth depends on the update cycle.

i Note**Observe line depth!**

Observe the maximum line depth for switches in store-and-forward mode according to the “Topology Check” section of the PI-PROFINET Commissioning Guidelines (PROFINET_Commissioning_8081) (www.profibus.com).

5.3 Installation Location and Additional Enclosure

The product is an open type device. It must only be installed within appropriate enclosures, cabinets or electrical operation rooms that fulfill at least the following requirements:

- Offer adequate protection against direct or indirect contact.
- Offer adequate protection against UV irradiation.
- Restrict access to authorized personnel and may only be opened with tools.
- Ensure the required pollution degree in the vicinity of the system.
- Prevent fire from spreading outside of the enclosure.
- Guarantee mechanical stability.

5.4 Ground Conductor and Protective Ground

The product must be grounded. The following options are available for this:

- Grounding screw
- CAGE CLAMP® connection

Do not operate the product without an appropriate ground conductor installed.

5.5 Mounting Position

All specifications and handling steps refer to the nominal mounting position. Deviating mounting positions affect, for example:

- Air circulation




Figure 7: Nominal Mounting Position

5.6 EMC Installation

- **Ground DIN-rails.**

Ground the DIN-rails to divert electromagnetic interference.

- **Use shielded cables for data and signal lines.**

Electromagnetic interference is reduced and signal quality increased. Measurement errors, data transmission faults and interference due to excessive voltage can be prevented!

- **Keep data and signal lines separate from interference sources.**

Route data and signal lines separately from all power supply cables and other sources of high electromagnetic emissions (e.g., frequency converters or drives).

- **Connect the cable shielding with the ground potential.**

Integrated shielding is mandatory to meet technical specifications regarding measurement accuracy. Establish the connection between the cable shielding and ground potential at the inlet of the cabinet or housing. This grounding allows induced interferences to dissipate and be kept away from devices in the cabinet or housing.

- **Improve shielding performance with a large contact area.**

A low-impedance connection between shielding and ground achieves better shielding performance. For this purpose, connect the shielding over a large surface area, e.g., using the WAGO Series 790 Shield Connection System. This is especially recommended for large-scale systems where equalizing or high impulse currents may occur.

Transport and Storage

The original packaging offers optimal protection during transport and storage.

- Store the product in suitable packaging, preferably the original packaging.
- Only transport the product in suitable containers/packaging.
- Make sure the product contacts are not contaminated or damaged during packing or unpacking.
- Observe the specified ambient climatic conditions for transport and storage.

Long-Term Storage

- For long-term storage, power must be applied to the product for five minutes at least every two years.

Installation and Removal

7.1 Mounting on the DIN-Rail



Figure 8: Mounting Product on DIN-Rail

1. Tilt the product slightly.
2. Place the product, with the DIN-rail guide, on the top edge of the DIN-rail.
3. Press the product onto the DIN-rail.
4. Push down until the product audibly snaps into place.

7.2 Removal from the DIN-Rail

CAUTION

Hot Surface!

The surface of the housing heats up during operation. Under special conditions (e.g., in the event of a fault or increased surrounding air temperature), touching the product may cause burns!

- Allow the product to cool down before touching it.




Figure 9: Removing the Product from the DIN-Rail

1. To remove the product, pull down the DIN-rail mount/removal latch. Use an operating tool for this purpose.
⇒ The product is now unlocked.
2. Tilt the product forward and unhook it from the DIN-rail.

7.3 Screw Installation on a Flat Surface

The product can be mounted directly on a flat surface using the boreholes on the rear of the device.

The surface must be able to bear at least 1.5 kg.

7.4 Dimensions of the Mounting Holes




Figure 10: Dimensions of the Mounting Holes

Anschließen

Solid conductors, as well as stranded and fine-stranded conductors with ferrules, are terminated by pushing them into Push-in CAGE CLAMP® Connectors. For all conductor types, an operating tool must be used to open the Push-in CAGE CLAMP®. Only one conductor may be connected to each clamping unit.

To connect a conductor, proceed as follows:

- ✓ You need an operating tool.
 - 1. Use the operating tool to press and hold the push-button next to the connection in question in order to open the Push-in CAGE CLAMP®.
 - 2. Insert the conductor into the corresponding connection opening (round housing opening).
 - 3. Release the push-button to close the Push-in CAGE CLAMP®.
- ⇒ The conductor is now securely clamped.




Figure 11: Connecting Conductor to Push-in CAGE CLAMP®

- ✓ You need an operating tool.
 - 1. Use the operating tool to press and hold the push-button next to the connection in question in order to open the Push-in CAGE CLAMP®.
 - 2. Remove the conductor.
 - 3. Release the push-button to close the Push-in CAGE CLAMP®.
- ⇒ The conductor is now detached.




Figure 12: Removing Conductor from Push-in CAGE CLAMP®

Decommissioning

9.1 Disposal and Recycling



WEEE Mark

Electrical and electronic equipment may not be disposed of with household waste. This also applies to products without this mark.



Electrical and electronic equipment contain materials and substances that can be harmful to the environment and health. Electrical and electronic equipment must be disposed of properly after use. Environmentally friendly disposal benefits health, protects the environment from harmful substances in electrical and electronic equipment and enables sustainable and efficient use of resources.

- Observe the national and local regulations for the disposal of electrical and electronic equipment, lithium-ion batteries, lead–acid batteries and packaging.
- Clear any data stored on electrical and electronic equipment.
- Remove lithium-ion batteries, lead–acid batteries or memory cards that are added to the electrical and electronic equipment.
- Wear appropriate personal protective equipment when removing the lithium-ion batteries/lead–acid batteries.
- Dispose of the removed lithium-ion batteries/lead–acid batteries according to your local waste regulations (e. g. collection boxes at the retail or local collection points).
- Have electrical and electronic equipment sent to a local collection point.
- Dispose of all types of packaging to ensure a high level of recovery, reuse and recycling.
- Transport packages from the B2B area can be taken back free of charge via a return system in accordance with the Packaging Act. Please contact our service provider Interseroh directly. The corresponding certificate can be found at: [🌐 corporate-certificates](#)
- Throughout Europe, Directives 2006/66/EC, 94/62/EC and 2012/19/EU (WEEE) apply. National directives and laws may differ.

Appendix

10.1 Technical Data, Approvals, Guidelines and Standards

The following approvals have been granted for the product:

	Conformity marking	
	Ordinary Locations	UL61010-2-201 (E175199)

The UL approval is only valid for DIN-rail mounting.

Note

Subject to changes!


Please also observe the further product documentation! You can generate the current datasheet at any time at: www.wago.com /<item number>.

Supplementary Technical Data

Table 1: Supplementary Technical Data

Standards	IEEE 802.3 Nway Auto-Negotiation
PROFINET	Conformance Class A (CC_A)
Topology	Tree, line
UL 61010	Use: indoor
	Pollution degree: 2
EMC immunity to interference	EN 61000-6-2
EMC emission of interference	EN 61000-6-4

See also

 Datenblatt_852-111/0000-0001 [▶ 24]



This unmanaged industrial ETHERNET switch (852-111/000-001) has 5 ETHERNET ports for easily setting up small- to medium-sized networks. Its slim design paired with a DIN-rail adapter simplifies installation in the control cabinet and provides high vibration and shock resistance. Additionally, automatic transmission rate detection (auto-negotiation) and automatic identification of the transmit and receive lines (Auto MDI-X) allow simple plug-and-play operation, saving time and money during commissioning.

Features:

- 5 ETHERNET ports 10/100 Mbit/s Autonegotiation
- Front-panel diagnostic LEDs
- Supports Auto-MDI/MDI-X functions
- Full/half-duplex transfer modes for each port
- Store-and-forward switching method
- Integrated address look-up table, supports 2000 absolute MAC addresses
- Overvoltage protection
- IEEE 802.3x flow control in full-duplex mode
- Prioritization of PROFINET data packets (EtherType=0x8892) per IEEE802.1p
- DIN-35 rail mounting

Technical data

Switching mode	Store-and-forward; non-blocking
Number of 100 Mbit/s ports	5
Communication standards	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x Flow Control IEEE 802.1p Prioritization
MAC table (size)	2000 addresses
Supply voltage	12 ... 48 VDC
Power consumption (max.)	2 W
Baud rate	Copper cable: 10/100 Mbit/s
Topology	Star
Indicators	Device: LED (PWR) green: Power supply; per port: LED (100, LNK/ACT) green: Status 100 Mbps, LNK/ACT port 1 ... 5

Connection data

Connection technology: communication/fieldbus	Copper cable: 5 x RJ-45
Connection technology: supply	1 x Built-in male connector: 231-433/001-000; included female connector (MCS Connectors): 231-103/026-000

Physical data

Width	23.4 mm / 0.921 inches
Height	109.2 mm / 4.299 inches
Depth	73.8 mm / 2.906 inches
Depth from upper-edge of DIN-rail	81 mm / 3.189 inches

Mechanical Data

Weight	203 g
Color	black
Housing material	Sheet steel

Environmental requirements

Ambient temperature (operation)	-40 ... +70 °C
Surrounding air temperature (storage)	-40 ... +85 °C
Protection type	IP30
Relative humidity (without condensation)	95 %
Mounting type	DIN-35 rail
Vibration resistance	per IEC 60068-2-6
Shock resistance	per IEC 60068-2-27
Fire load	0 MJ

Commercial data

PU (SPU)	1 pcs
Country of origin	TW
GTIN	4066966216288
Customs tariff number	85176200000

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

10.2 RJ-45 Cable

Use standard ETHERNET cables when connecting the product. WAGO recommends using cables of at least category 5e with the following pin assignment:

Table 2: RJ45 cable

Contact	Designation		Pair	Color
	4-Wire	8-Wire		
1	TD	D1+	2	White/orange
2	TD-	D1-	2	Orange
3	RX+	D2+	3	White/green
4	Not assigned	D3+	1	Blue
5	Not assigned	D3-	1	White/blue
6	RX-	D2-	3	Green
7	Not assigned	D4+	4	White/brown
8	Not assigned	D4-	4	Brown

10.3 Protected Rights

- Adobe® and Acrobat® are registered trademarks of Adobe Systems Inc.
- Android™ is a trademark of Google LLC.
- Apple, the Apple logo, iPhone, iPad and iPod touch are registered trademarks of Apple Inc. registered in the USA and other countries. “App Store” is a service mark of Apple Inc.
- AS-Interface® is a registered trademark of the AS-International Association e.V.
- BACnet® is a registered trademark of the American Society of Heating, Refrigerating and Air Conditioning Engineers, Inc. (ASHRAE).
- Bluetooth® is a registered trademark of Bluetooth SIG, Inc.
- CiA® and CANopen® are registered trademarks of CAN in AUTOMATION – International Users and Manufacturers Group e.V.
- CODESYS is a registered trademark of CODESYS Development GmbH.
- DALI is a registered trademark of the Digital Illumination Interface Alliance (DiiA).
- Docker and the Docker logo are trademarks or registered trademarks of Docker, Inc. in the United States and/or other countries. Docker, Inc. and other parties may also have trademark rights in other terms used herein.
- EtherCAT® is a registered trademark and patented technology licensed by Beckhoff Automation GmbH, Germany.
- ETHERNET/IP™ is a registered trademark of the Open DeviceNet Vendor Association, Inc (ODVA).
- EnOcean® is a registered trademark of EnOcean GmbH.
- Google Play™ is a registered trademark of Google Inc.
- IO-Link is a registered trademark of PROFIBUS Nutzerorganisation e.V.
- KNX® is a registered trademark of the KNX Association cvba.
- Linux® is a registered trademark of Linus Torvalds.
- LON® is a registered trademark of the Echelon Corporation.
- Modbus® is a registered trademark of Schneider Electric, licensed for Modbus Organization, Inc.
- OPC UA is a registered trademark of the OPC Foundation.
- PROFIBUS® is a registered trademark of the PROFIBUS Nutzerorganisation e.V. (PNO).

- PROFINET® is a registered trademark of the PROFIBUS Nutzerorganisation e.V. (PNO).
- QR Code is a registered trademark of DENSO WAVE INCORPORATED.
- Subversion® is a trademark of the Apache Software Foundation.
- Windows® is a registered trademark of Microsoft Corporation.

List of Tables

Table 1	Supplementary Technical Data.....	23
Table 2	RJ45 cable.....	26

List of Figures

Figure 1	Front View	12
Figure 2	Top View	12
Figure 3	Type Plate (Example)	13
Figure 4	Power Supply Connection	14
Figure 5	Status LED	14
Figure 6	LED Indicators – Network Connections	14
Figure 7	Nominal Mounting Position	16
Figure 8	Mounting Product on DIN-Rail	19
Figure 9	Removing the Product from the DIN-Rail	19
Figure 10	Dimensions of the Mounting Holes	20
Figure 11	Connecting Conductor to Push-in CAGE CLAMP®	21
Figure 12	Removing Conductor from Push-in CAGE CLAMP®	21

WAGO GmbH & Co. KG

Postfach 2880 · D - 32385 Minden
Hansastraße 27 · D - 32423 Minden

✉ info@wago.com
🌐 www.wago.com

Headquarters	+49 571/887 – 0
Sales	+49 (0) 571/887 – 44 222
Order Service	+49 (0) 571/887 – 44 333
Fax	+49 571/887 – 844169

WAGO is a registered trademark of WAGO Verwaltungsgesellschaft mbH.
Copyright – WAGO GmbH & Co. KG – All rights reserved. The content and structure of the WAGO websites, catalogs, videos and other WAGO media are subject to copyright. Distribution or modification of the contents of these pages and videos is prohibited. Furthermore, the content may neither be copied nor made available to third parties for commercial purposes. Also subject to copyright are the images and videos that were made available to WAGO GmbH & Co. KG by third parties.